

SAFETY DATA SHEET

Revision Date 29-May-2018

Version 2

Odor Alcohol

1. IDENTIFICATION				
Product identifier Product Name	Rain-X Glass Cleaner			
Other means of identification Product Code Document	10516 SKU: 63018, 63019, 800001679, 800001680			
Recommended use of the chemical Recommended Use Uses advised against	and restrictions on use No information available. No information available			
Details of the supplier of the safety Supplier Address ITW Global Brands 16200 Park Row, Suite 120 Houston, TX 77084 Distributor	<u>data sheet</u> <u>Manufacturer Address</u>	Manufactured and Distributed by: May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5		
Company Phone Number 24-hour emergency phone number	1-855-888-1988 (CHEMTREC) 1-800-424-9300 or 1-703-527-3 (RMPDC) 1-877-504-9352 (U.S.)	Telephone: (800) 924-6994		
E-mail address	SDS@itwgb.com			
	2. HAZARDS IDENTIFICATION			
<u>Classification</u>				
OSHA Regulatory Status This chemical is considered hazardous	s by the 2012 OSHA Hazard Communication St	andard (29 CFR 1910.1200)		
Flammable liquids		Category 4		
Label elements				
	Emergency Overview			
<u>Signal word</u> Warning				
Combustible liquid				

Precautionary Statements - Prevention

Appearance Clear

Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wear protective gloves/protective clothing/eye protection/face protection

Physical state Liquid

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Causes mild skin irritation

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
2-BUTOXYETHANOL	111-76-2	1 - 5
Isopropanol	67-63-0	1 - 5

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.	
Skin contact	None under normal use conditions. Wash with plenty of water. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.	
Inhalation	None under normal use conditions. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors or decomposition products.	
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.	
Self-protection of the first aider	Use personal protective equipment as required.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	See section 2 for more information.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable extinguishing media

Dry chemical, CO2, water spray or regular foam, Use, Dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Will not burn or support combustion. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.	
Environmental precautions		
Environmental precautions	See section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.	
Methods and material for containm	ent and cleaning up	
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Ensure adequate ventilation. Collect spillage. Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.	
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.	
	7. HANDLING AND STORAGE	
Precautions for safe handling		
Precautions for safe handling Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).	
_	exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).	
Advice on safe handling	exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).	
Advice on safe handling Conditions for safe storage, includ	 exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). ing any incompatibilities Keep in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away 	

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-BUTOXYETHANOL	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m ³	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³
		(vacated) TWA: 120 mg/m ³	-
		(vacated) S*	
		S* ´	
Isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	-

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations Ventilation systems
	ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses or goggles if splashing is likely to occur. Tight sealing safety goggles.
Skin and body protection	None under normal use conditions.
Respiratory protection	Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Clear	
Odor	Alcohol	
Odor threshold	No information available	
Property	Values	Remarks • Method
рН	7	
Melting point / freezing point	No information available	
Boiling point / boiling range	86 °C / 187 °F	
Flash point	68 °C / 154 °F	Cleveland Open Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	Soluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	

Decomposition temperature	
Kinematic viscosity	
Dynamic viscosity	
Explosive properties	
Oxidizing properties	

Other Information

Softening point Molecular weight VOC Content (%) Density Bulk density No information available No information available No information available No information available No information available

No information available No information available 2.4 1000 g/cm3 @ 25 °C No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

None known based on information supplied. Heat, flames and sparks.

Incompatible materials

None known based on information supplied

Hazardous Decomposition Products

None under normal use conditions

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Expected to be low order of toxicity under normal conditions of use. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Eye contact	May cause eye irritation with susceptible persons.
Skin contact	Prolonged contact may cause redness and irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-BUTOXYETHANOL	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
111-76-2			
Isopropanol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
67-63-0			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No informatio				
Germ cell mutagenicity	No informatio	No information available.			
Carcinogenicity	The table bel	ow indicates whether each	n agency has listed any ing	redient as a carcinogen.	
Chemical Name	ACGIH	IARC	NTP	OSHA	

2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-
Isopropanol	-	Group 3	-	Х
67-63-0				
ACGIH (American Confe	rence of Governmental li	ndustrial Hygienists)		
A3 - Animal Carcinogen				
IARC (International Agen		cer)		
Group 1 - Carcinogenic to				
Not classifiable as a huma	0			
OSHA (Occupational Safety and Health Administration of the US Department of Labor)				
X - Present				
Chronic toxicity		May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.		
Target Organ Effects				
	system, Skin.			
The following values are calculated based on chapter 3.1 of the GHS document				
ATEmix (oral)	-			
ATEmix (dermal)	65829 mg/kg			
ATEmix (inhalation-du	0 0			
ATEmix (inhalation-va	, ,			
12. ECOLOGICAL INFORMATION				

Ecotoxicity

0.5 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	Partition coefficient
2-BUTOXYETHANOL 111-76-2	0.81
Isopropanol 67-63-0	0.05

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Recover or recycle if possible. Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Isopropanol	Toxic

67-63-0	Ignitable

14. TRANSPORT INFORMATION

DOT Proper shipping name:	Not regulated
IATA Proper shipping name:	Not regulated
IMDG Proper shipping name:	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Not determined
IECSC	Not determined
KECL	Not determined
PICCS	Not determined
AICS	Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	1.0
Isopropanol - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
WATER	-	-	X
7732-18-5			
2-BUTOXYETHANOL	X	X	X
111-76-2			
Isopropanol	X	X	Х
67-63-0			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials, B3 - Combustible liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA HMIS	Health hazards 1 Health hazards 1	Flammability 2 Flammability 2	Instability 0 Physical hazards 0	- Personal protection B	
NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)					
Revision Date Revision Note	29-May-20	118 3			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet